




# **EZCreaser**



## Auto setups of all the following:








# Get the features and speed you need, in an easy-to-use, affordable machine.







Rotary Perf and Score



Micro Lateral Adjust

The COUNT™ EZCreaser gives you the robust features you need at an economical price, for lower to medium volume creasing, scoring and perforating. You get the speed and reliability of a top-feed automatic friction paper feeder, with smooth, consistent operation. You get a machine that's simple to set up, and easy for anyone to use with the popular COUNT touch-screen operation, and one-touch automatic set-ups built in. And you get even higher speeds for operating in perf mode, with 5 interchangeable perf options (including micro-perf).



### **EZCreaser**



# MADE IN USA

### **Features**

- Offers a reliable top-load friction paper feed.
- · Rotary actuated impact creasing.
- · Automated Distance Recognition allows auto setups for your most common creases and corresponding folds, including perfect bind.
- · Comes standard with rotary perf wheel assembly.
- Optional micro-perf and score wheel assemblies are available.
- Includes micro-lateral adjustable feed rails and sheet counter (batch and total counting).
- Add the COUNT™ KF-200 or another inline folder.
- Add the optional inline transport to feed directly into the COUNT™ CountCoat or other UV coaters.
- Two-sided creasing die- one side has a narrow crease and the other a wide crease for heavier stock- to change, simply remove the die and flip it over.
- User-friendly touch screen for easy set up and control of the machine.

### **Automatic Set-Up for Many Common Folds**

Half

Tri-Fold

Z-Fold

Letter Fold

Roll Fold

Gate Fold

Double Gate Fold

**Double Parallel Fold** 

Perfect Bind - No Hinge

Perfect Bind - Single Hinge

Perfect Bind - Double Hinge

### **Specifications**

Model: EZCreaser

Model No.: EZCREASER

Paper Feed: Friction

Weight: 144 lbs (66 kg)

**Max Compression Crease:** 

(sheets per hour) Max Rotary Perf/Score Speed: 12,000

(sheets per hour)

Paper Weight Range:

(gsm)

**Dimensions**: 47.0 L x 29.0 W x 22.0 H in

 $(119.4 \times 74.0 \times 56.0 \text{ cm})$ 

Max Sheet Size: 18 x 24 in (45.7 x 50.8 cm)

Min Sheet Size: 4.5 x 4.5 in (7.6 x 12.7 cm)

Electrical: 115 V, 60 Hz, 20 A or 230 V, 50 Hz, 20 A

Made in: U.S.A.





260-563-0621 | Fax: 260-563-4575 www.martinyale.com

