

# OMATION<sup>®</sup>

Enhanced Envelopener with Sorting Capabilities



**Model 306<sup>™</sup>**



**Model 306s<sup>™</sup>**

**High Volume, High Speed Envelope Opening  
and Sorting for All Types of Mail**

**OPEX<sup>®</sup>**  
CORPORATION

## OMATION MODEL 306™

### High-Speed Opening

- Operates at up to 40,000 envelopes per hour

### Three Mail Tray Supports

- Permits optimized work flow & improved ergonomics

### Operator Controlled Software Interface

- Provides numerous job settings
- Supports multiple operators & languages with password protection
- Presents an easy-to-read backlit LCD display

### Automatic Jam Detection

- Reduces damage while making jam clearing easier

### Automatic Chaff Collection

- Provides a clean workspace, jam prevention, & reduced static buildup

### Milling Cutter

- Offers 8 cut-depths plus “No-Cut” position

## Model 306 and 306s Optional Features

### Batching

- Groups items into pre-selected lot sizes

### 90° Powered Conveyor

- Adds capacity & larger space to manage output

### Reports Printer

- Produces a variety of statistics reports for monitoring machine performance

### High-Speed Inkjet Printer

- Prints a variety of custom strings, date & time, sequential numbering & ID Tag barcodes
- Prints up to 4 lines



### OPEX World Headquarters

305 Commerce Drive  
Moorestown, NJ 08057-4234  
United States

Tel: +1 856.727.1100  
Fax: +1 856.727.1955

[www.opex.com](http://www.opex.com)

### OPEX United Kingdom

Carrington Business Park  
Carrington  
Manchester, England  
M314YR

Tel: +44 0161.776.4033  
Fax: +44 0161.776.2663

## OMATION MODEL 306s™

Coupled with enhanced sorting capabilities, the Model 306s is a perfect fit for a wide variety of applications. Envelopes can be output to two locations based on programmable criteria such as thickness, length, and height. With its ability to identify “primary mail” from “secondary mail,” the Model 306s helps to ensure maximum productivity by opening and sorting envelopes in a single pass.

### Sort Wizard

- Intuitive & easy-to-use operator interface for job setup



## 306 Base Model Specifications:

Length	47.75" (121.285 cm)
Depth	21" (53.34 cm)
Height	58" (147.32 cm)
Weight	245 pounds
Power	115 VAC, 60HZ, 8.5A 230 VAC, 50HZ, 5.5A
BTU	3338 BTU/h (115VAC) 4317 BTU/h (230VAC)
Speed	Up to 40,000 / hour
Envelope Sizes & Types	Lengths up to 13.5" (34.29 cm) (including overnight packs)
Thickness	Up to 0.50" (1.27 cm)
Depth of Cut	From 0.01" (0.03 cm) from envelope edge up to 0.125" (0.32 cm) in depth
Feeder Hopper Capacity	Up to 400 envelopes
Stand & Waste Bin	Included

### OPEX France

3 avenue du Canada  
Parc Technopolis – ZA  
COURTABOEUF  
Bâtiment EPSILON  
91940 – LES ULIS – France  
Tel: +33 01.60.92.40.40

### OPEX Germany

Max-Planck-Ring 39  
65205 Wiesbaden-Delkenheim  
Germany  
Tel: +49 6122.927.8883  
Fax: +49 6122.927.8885